

Functional Style

This heavy duty system provides ample opportunity for upgrades. Choose white or satin nickel finish. Add stylish wood grains with Heirloom Select cabinets and accessories. Its fast and easy to install.



Rubbermaid **FastTrack**

Rubbermaid **FastTrack**
ADJUSTABLE SHELVING
SUPERIOR STRENGTH

RAILS

For use with FastTrack® Uprights.

40" FastTrack® Rail – White	FG3Q7000WHT
40" FastTrack® Rail – Satin Nickel	FG3Q7000SNCKL
80" FastTrack® Rail – White	FG3Q7100WHT
80" FastTrack® Rail – Satin Nickel	FG3Q7100SNCKL

UPRIGHTS

Use to support brackets for shelving.

25" FastTrack® Upright – White	FG3Q7300WHT
47 1/2" FastTrack® Upright – White	FG3Q7400WHT
47 1/2" FastTrack® Upright – Satin Nickel	FG3Q7400SNCKL
70" FastTrack® Upright – White	FG3Q7500WHT
70" FastTrack® Upright – Satin Nickel	FG3Q7500SNCKL
81 1/4" FastTrack® Upright – White	1780151
81 1/4" FastTrack® Upright – Satin Nickel	1780152

BRACKETS

To support Rubbermaid® Wire Shelving.

12" Bracket – use on all 12" shelving plus 16" Wardrobe and FreeSlide shelving	
12" Bracket – White	FG3Q66LWWHT
12" Bracket – Satin Nickel	FG3Q6600SNCKL
16" Bracket – use on 16" Linen and TightMesh shelving	
16" Bracket – White	FG3Q67LWWHT
16" Bracket – Satin Nickel	FG3Q6700SNCKL
20" Bracket – use on 20" TightMesh shelving	
20" Bracket – White	FG3Q68LWWHT
20" Bracket – Satin Nickel	FG3Q6800SNCKL

RAIL HARDWARE

For mounting FastTrack® rail. Contains seven 12x2" screws, six 10x2" screws, seven anchors, four large plastic caps (5504), 20 small plastic caps (5503), and four extra small plastic caps (FG3P3800WHT).

FastTrack® Hardware Kit	FG3P56LWWHT
-------------------------	-------------

**Differentiate yourself with Rubbermaid
Closet Systems – call 1-877-533-1197**

RubbermaidPro.com

1913875



RubbermaidPro.com

Rubbermaid

Sturdy & Versatile

Rubbermaid® FastTrack® is ideal for storage spaces requiring greater flexibility and strength. FastTrack® is completely adjustable and works with all Rubbermaid® shelving types.



GREENGUARD

PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818

GOLD



The only GREENGUARD certified wire shelving

Upgraded Shelving Options Are Easy As 1,2,3.

Step 1



Install rail at desired height using #12 x 2 1/2" screws and drywall anchors provided (88" is standard height measured from top of rail). Use 1/8" bit to drill pilot holes for screws going into studs, and use 1/4" bit to drill holes for drywall anchors.

Step 2



Hang uprights from the rail, spaced no more than 32" apart. Drill holes for stud or wall anchors and secure each upright in two locations using #10 x 2" or #12 x 2 1/2" screws (both size screws work with wall anchor).

Step 3



Insert brackets into uprights at desired locations and lock shelving into brackets.

Storage Made Easy

- Install any closet or pantry with minimum drilling
- Uprights don't require studs locations for installation
- Brackets and shelves lock into place for security and personalization
- FastTrack® can be adjusted as storage needs change without additional hole drilling

Storage Made Strong

Weight capacities:

- 100 lbs. * Per bracket (any size)
- 300 lbs. ** Per upright (any size)

*When mounting the rail properly into the studs.

**Additional weight holding capacity can be gained by attaching uprights to studs with screws.

***Cut shelving with no more than 8" of unsupported shelf at each end.